



## Model 5100HD Gas Analyzers for Measuring O<sub>2</sub> in Process Gas

Based on Tunable Diode Laser Absorption Spectroscopy (TDLAS)

*Model 5100HD, GP, Class I, Div 2  
ATEX/IEC Ex Zone 2*



*Model 5100HD Class I, Div 1  
ATEX/IEC Ex Zone 1*



*Model 5100HD uses sealed reference cells for continuous on-line analyzer verification and offers high specificity, sensitivity and extremely fast response speeds.*

### Features and Benefits

- ▶ **Noncontact Measurement**  
The sample has no contact with the optical measuring device which minimizes maintenance
- ▶ **All Digital Signal Processing**  
32-bit microcontroller capable of sophisticated signal processing
- ▶ **Web-Based Interface**  
To interrogate the analyzer remotely, all you need is the IP address of the analyzer
- ▶ **Connectivity**  
Modbus, Ethernet, dry contacts and analog
- ▶ **Real-Time Performance Monitoring**  
Laser line-lock and span verification using internal reference cell
- ▶ **NEMA 4X Enclosure to house the electronic components**  
Designed for outdoor installation
- ▶ **Fully-Integrated Sample Handling**  
Standard feature
- ▶ **Resistant to Contamination**  
No interference from gas phase amines, glycol, methanol, and mercaptans
- ▶ **Hazardous Area Options**  
ATEX/IEC Ex Zone 2  
(Pending) NEC/CEC: Class I, Div 2, Groups A,B,C,D; ATEX/IEC Ex Zone 1, IIB+H<sub>2</sub>, T3

# Model 5100HD Gas Analyzers

## Specifications

**Typical Operating Range:** 0-1% and 0-25%

**Accuracy:** 0.1% (v/v) or 2% of reading, whichever is greater

**Repeatability:** 0.1% (v/v) or 2% of reading, whichever is greater

**Linearity:** 0.1% (v/v) or 2% of reading, whichever is greater

**Environment:**

**Ambient Temperature:** -20°C to +50°C (-4°F to 122°F).

**Electrical Classification:**

ATEX/IEC Ex Zone 2  
(Pending) NEC/CEC: Class I, Div 2,  
Groups A,B,C,D; ATEX/IEC Ex Zone 1,  
IIB+H<sub>2</sub>, T3

**Relative Humidity:** 0% to 90%, non-condensing

**Sample Flow Rate:** 1 to 10 SLPM recommended (2 - 20 SCFH)

**Sample Cell Pressure:**

70 to 170 kPa absolute (10-25 psia)  
For higher pressures, consult AMETEK.

**Sample Cell Temperature:**

The horizontal cell is located in an oven with sample tubing and filter which has variable temperature options depending on application requirement. Note that sample must be presented to the analyzer in the gas phase. The analyzer may maintain gas phase at the appropriate temperature but should not be used to vaporize liquid sample.

**Speed of Response:**

< 1 second photometric response. Total system response is dependent on sample flowrate.

**Outputs:**

4-line x 20-character alphanumeric VF display.

**Fast Ethernet** (IEEE802.3)

**RS-485** serial port, isolated (supports Modicon Modbus RTU)

(1) isolated 4-20 mA loop-powered analog output

(4) dry relay contacts. Contact rating 30 VAC, 60 VDC, 100 VA resistive

**Electrical Requirements:**

120 VAC (108-132V); 47-63 Hz, or 240 VAC (216-264V), 47-63 Hz  
24 VDC also available, consult factory

**Power Requirements:**

Model 5100HD: 450W with optional heater

**Physical Dimensions (HxWxD):**

Model 5100HD:  
67.4 cm x 83.0 cm x 30.5 cm  
(26.5 in. x 32.7 in. x 12.0 in.)

Model 5100HD Atex Zone 1:  
64.8 cm x 114.3 cm x 43.6 cm  
(25.5 in. x 45.0 in. x 17.1 in.)

**Weight:**

Model 5100HD:  
59 Kg (130 lb)

Model 5100HD Atex Zone 1:  
114 Kg (250 lb)

**Enclosure:** IP-65, NEMA 4X

TDLAS



150 Freeport Road, Pittsburgh, PA 15238  
Ph. +1-412-828-9040, Fax +1-422-826-0399  
www.ametekpi.com



© 2012, by AMETEK, Inc.  
All rights reserved. Printed in the U.S.A.  
F-0368 Rev. 3 (1013)

One of a family of innovative process analyzer solutions from AMETEK Process Instruments.  
Specifications subject to change without notice.

**SALES AND MANUFACTURING:**

**USA - Delaware**  
455 Corporate Blvd., Newark DE 19702 • Tel: +1-302-456-4400, Fax: +1-302-456-4444

**USA - Oklahoma**  
2001 N. Indianwood Ave., Broken Arrow OK 74012 • Tel: +1-918-250-7200, Fax: +1-918-459-0165

**CANADA - Alberta**  
2876 Sunridge Way N.E., Calgary, AB T1Y 7H9 • Tel: +1-403-235-8400, Fax: +1-403-248-3550

**WORLDWIDE SALES AND SERVICE LOCATIONS:**

**USA - Texas**  
Tel: +1-713-466-4900, Fax: +1-713-849-1924

**CHINA**  
Beijing / Tel: 86 10 8526 2111, Fax: 86 10 8526 2141  
Chengdu / Tel: 86 28 8675 8111, Fax: 86 28 8675 8141  
Guangzhou / Tel: 86 20 8363 4768, Fax: 86 20 8363 3701  
Shanghai / Tel: 86 21 5868 5111, Fax: 86 21 5866 0969

**FRANCE**  
Tel: 33 1 30 68 89 20, Fax: 33 1 30 68 89 29

**GERMANY**  
Tel: 49 21 59 91 36 0, Fax: 49 21 59 91 3639

**INDIA**  
Tel: 91 80 6782 3200, Fax: 91 80 6782 3232

**SINGAPORE**  
Tel: 65 6484 2388, Fax: 65 6481 6588